

# Pro Mod Rules Amendments

## 09-10-2024

### Twin Turbo Big Block:

5.0" bore space 88mm max ~~2500lbs minimum~~ 2550lbs minimum (Added 50lbs)

5.0" bore space 94mm max ~~2550lbs minimum~~ 2600lbs minimum (Added 50lbs)

5.0" bore space 98mm max ~~2625lbs minimum~~ 2725lbs minimum (Added 100lbs)

Stepped compressor wheel (**Not Allowed**)

(Add 25lbs for 4.9 Bore space)

(Add 50lbs for 5.3 bore space)

Add 25lbs. for transmission with four (4) or more forward gears – converter-driven combinations only. Addition does not apply to clutch combinations.

(Add 50lbs lock-Up Transmissions also if you have a lock-up in the car no matter what you have to run the weight - no other power adder) Manipulation of transmission or convertor pressure or volume, other than at the starting line, is prohibited on any non-lockup combination. Pressure manipulation control must be disarmed upon the release of the transbrake, or any other device used, when launching the vehicle for non-lockup combination)

Recirculation slot (MAP Groove) may be a maximum of .3125 inches and leading edge of slot must be within .625 inches of the tip (front) of the compressor wheel blade. Contour of the compressor blade from inducer to exducer must have a continuous radiused shape with no sharp angle changes. Exotic designed turbos prohibited.

(No test or prototype of any kind allowed)